(51) International Patent Classification ^{6} : H04L 29/06, 12/66, 12/64	A1	(11) International Publication Number: WO 99/04540
		(43) International Publication Date: 28 January 1999 (28.01.99)

(54) Title: COMMUNICATION SYSTEM

(57) Abstract

A communication system for establishing communication between two end points (7, 12). The system comprises at least two communication media (1, 2) operating in accordance with different communication protocols and connected to respective ones of the end points in use. An interface (3) couples together the two communication media (1, 2). A control system (24, 27) is connected to each of the end points (7, 12) and to the interface (3) and is responsive to a request to establish a communication connection between the end points to configure the interface (3) and the end points (7, 12) such that a connection path is defined between the end points, via the communication media along which messages can subsequently be sent.

COMMUNICATION SYSTEM

The invention relates to a communication system for establishing communication between two end points such as two end station ports, two devices within an end station, or the like where each end point is coupled to a respective communication medium, with each medium operating in accordance with a different communication protocol.

In recent years, local area networks (LANs) have been developed to handle the communication of data between end stations, such as PCs, using certain network protocols such as token ring or ATM. Each different network protocol handles data in a different format and as a consequence, the data of one protocol is incompatible with that of another. This prevents direct communication between end stations operating under different protocols. Communication can therefore only be achieved indirectly by having an intermediate router stage. This determines the route the data must take through the subsequent network and alters the data format from that of original protocol to that of subsequent network.

For a given network connection, this method can result in data being sent over different routes within the network. This can result in the data being delivered out of sequence. This is generally unacceptable for real time data, such as audio and video, due to the resulting delays caused by the additional processing required to resequence the received data at the receiving end station.

Examples of known methods are described in WO-A-97/16007, US-A-5208811 and JP-A-62130049.

In accordance with one aspect of the present invention, we provide a communication system for establishing communication between two end points, the system comprising at least two communication media operating in accordance with different communication protocols and connected to respective ones of the end points in use, an interface for coupling together the at

2

least two communication media, and a control system connected to each of the end points and to the interface, wherein the control system is responsive to a request to establish a communication connection between the end points

5   to configure the interface and the end points such that a connection path is defined between the end points via the communication media along which messages can subsequently be sent.

In accordance with a second aspect of the present

10   invention, we provide a method of operating a communication system for establishing communication between two end points, each end point being coupled to a respective communication medium, the media operating in accordance with different communication protocols and being coupled

15   together by an interface, the method comprising configuring the interface and the end points such that a connection path is defined between the end points, via the communication media along which messages can subsequently be sent.

20   We have devised a method and apparatus that allows direct communication between end points located on media operating under different communication protocols.

The end points may be constituted by end stations such as PCs, servers and the like or by devices within an end

25   station, for example a telephone interface card, MVIP card or NIC card. Where the end points comprise end stations, the media will comprise communication networks while if both end points comprise devices within the same end station then the communication media will comprise

30   communication buses. More generally, the invention enables connection to be achieved between a device within an end station and another device within another end station in which case the communication media will comprise a mixture of buses and networks.

35   In order to transfer data from one end point to another, it is necessary for the data transferred to be addressed to the receiving end point. Because the format

of data packets used by any network or bus protocol differs between protocols, it is not possible to address the end point of a network or bus operating under a different protocol unless there is a higher level of control which resolves incompatible addresses.

The present invention operates to overcome this problem by configuring the end points and the interface between the two media to define a connection path between the end points, via the media, prior to sending any data over the media. As a consequence, the data that is sent over the media need not specify the address of the end point to which it is sent but rather can be simply sent to follow a pre-specified route that will terminate at the end point required. This enables data to be transferred directly from one end point to another end point, across LANs and buses operating different protocols.

As a direct consequence of this, it is possible for forms of communication such as voice, video and the like to be transferred as data directly from one end point to another.

Typically, the control system of the communication system comprises a connection controller coupled to at least the interface and the end points for determining possible connection paths between the end points. The connection controller then selects one of the possible connection paths and configures the end points and interface to establish the connection path. The use of a connection controller provides an overall view of the media and the connection of the end points and interfaces thereto. From this, it is possible to determine the possible connection paths that could be made and from these the connection controller selects the most preferable route to connect end points.

Preferably, the control system comprises a number of local controllers, with each local controller being coupled to the connection controller and to one of the end points or the interface. The local controllers then configure the

4

respective end point or interface in accordance with a request from the connection controller. This optimises the operation of the system by requiring that the connection controller merely generates a request that a certain
5   connection route be established. The local controllers then ensure that the relevant end points and interfaces are configured as required. Whilst all this could be carried out by the connection controller, this would increase the amount of information that the connection controller would
10 have to handle resulting in a slowing down in the establishment of a connection.

Preferably, the local controller provides information on the local configuration, such as cost and configuration, to the connection controller to aid the connection
15 controller in establishing the optimum route.

The end points may be of any form, but typically they are suitable for forms of communication such as voice, video communication and the like.

Preferably, the control system also has a call
20 controller coupled to end points and the connection controller. The term "call" is to be understood to include any type of communication including machine-to-machine, voice-to-voice, machine-to-voice and the like. The call controller is used to receive a request to establish
25 communication between the end points and subsequently cause the connection controller to determine possible connection paths and then select one of the possible connection paths. Again, this could be directly achieved by the connection controller but it is preferable to have a separate system
30 thereby reducing the processing requirements placed on the connection controller and providing an abstraction between calls and the connection between physical devices.

Typically, the method of operating the communication system involves determining possible connection paths
35 between the end points, selecting one of the possible connection paths and configuring each end point and the interface to establish a connection between the end points,

via the media, using the selected connection path. It will be realised, however, that the method could involve simply selecting any path that connects the two end points although this may result in a busy path being selected

5 whilst a less busy path is available.

In the case where the connection controller is coupled to each of the end points, the method typically involves monitoring the end points for a request to establish communication between the end points, determining possible

10 connection paths between the end points, selecting one of the possible connection paths and configuring the end points and the interfaces to establish a connection between the end points, via the media, using the selected connection path.

15 An example of a communication system according to the invention will now be described with reference to Figure 1 which is a schematic diagram of the communication system.

Figure 1 shows a communication system including two local area networks (LANs) 1,2. In this example, LAN 1 is

20 an Ethernet network while LAN 2 is ATM. However, this invention is applicable to any combination of heterogeneous networks (or buses). The LANs 1,2 are coupled together by an interface 3. The interface 3 comprises two network interface cards (NICs) 4,5 connected to a bus 6. The bus

25 6 operates to pass data between the NICs 4,5. In this example, NIC 4 is configured to communicate over an Ethernet network while NIC 5 is configured to communicate over an ATM network.

The LAN 1 is also coupled to an end station 7 by means

30 of a NIC 8. The end station will generally be a personal computer suitable for carrying out voice and video communication as required. The NIC 8 is connected to a telephone interface card 9 by means of a bus 10. This connection is shown only schematically. More details will

35 be described with reference to the end station 12. The telephone interface card 9 is connected to a telephone 11.

The LAN 2 is also coupled to an end station 12 by means of a NIC 13. The NIC 13 is connected to a telephone interface card 14 via a PC data bus 15, an MVIP card 28, and a MVIP bus 30. The telephone interface card 14 is connected to a telephone 16. The buses 6,10,15,30, NICs 4,5,8,13 and the MVIP card 28 are coupled to local connection controllers 21,22,23,31,17,18,19,20,29 respectively which are coupled to a central connection controller 24. The cards 9,14 are coupled to local call controllers 25,26 respectively which together with the central connection controller 24 are coupled to a central call controller 27.

The following example of this invention is based on establishing a telephone connection between the two end stations 7,12 and involves coupling heterogeneous networks and buses.

On initialisation of the end stations 7,12 and the interface 3, the devices for controlling the media sources (telephones 11,16), in this example the cards 9,14, register with the central call controller 27 via the respective local call controllers 25,26. The cards 9,14 provide call controller 27 with information relating to the startup and stop routines of the cards, the media each card supports and the relative priority assigned to the media. Each end station 7,12 registers its designated ID with the connection controller 24. The network endpoints, in this example the NICs 4,5,8,13 and the end station endpoints (MVIP card 28) register with the connection controller 24 via their respective local connection controllers. The NICs 4,5,8,13 provide the connection controller 24 with information on the attached network type, and a cost associated with using the endpoint.

In order for a call to be made from end station 7 to end station 12, a user of the end station 7 will input a request, using either the phone 11 to dial a predetermined number assigned to end station 12 or by using a phone application (not shown) running on end station 7. The

request will include information on the type of media, which in this example will be voice. The end station 7 will pass, via the local call controller 25, this request to the call controller 27. The call controller 27 will assign this call with an identification number (Call ID). The call controller 27 checks the status of end station 12. If the end station 12 can accept the call, for example end station 12 has a phone 16 connected which is not in use, the call controller 27 sends end station 12 an alert signal which will instruct the local call controller 26 to instruct the card 14 to ring the phone 16. If phone 16 is answered, the call controller 27 instructs the cards 9,14 to start and for each card to create a source and sink to allow a full duplex connection to be established between the cards 9,14. The phonecard 9 requests, via the local call controller 25, the connection controller 24 to establish a call. Included with the request is information on the end station ID and Call ID, having been provided to the local call controller 25 by the call controller 27. The card 14 requests the connection controller 24 to establish a call providing the connection controller 24 with the call ID provided by the call controller 27 and the end station ID. As the call ID from end stations 7 and 12 will be the same, the connection controller 24 is able to establish that end stations 7 and 12 are the endpoints for this given call.

As the connection controller 24 now knows the end points for this particular call, the connection controller 24 is able to determine the most appropriate route to establish the connection. Having established the route, the connection controller 24 instructs the local connection controllers to set up a data path between end stations 7 and 12. In this example, the local connection controller 22 will, for this call, establish a connection between the designated source and sink on the card 9 with the NIC 8. The local connection controllers 19 and 17 establish a connection between the NICs 4 and 8 over the network 1

8

using the Ethernet protocol. To set up this connection, the connection controller 24 provides NIC 8 with NIC 4 network address and vice versa. Local connection controller 21 will establish a connection between NICs 4
5   and 5 over the bus 6. The local connection controllers 18 and 20 establish a connection between the NICs 5 and 13 over the network 2 using the relevant ATM NIC addresses provided by connection controller 24. Local connection controller 23 will establish a connection between NIC 13
10   and the MVIP card 28 over the PC data bus 15 while local controller 31 establishes a connection between the MVIP card 28 and phone card 14 via MVIP bus 30. Each connection is associated with the call ID provided by the call controller 27. Each connection is dependent on the
15   relevant network or bus protocol, for example over the ATM network a VP/VC will be assigned for this call. Once the connection path has been established, data will flow bi-directionally between phone card 9 and 14.

    In more detail, each local connection controller
20   maintains, for its given domain, a routing table for each call that has been set up, i.e. for each call the relevant local connection controller maintains a table associating the connections of the different media. For example, if a user makes a call using telephone 11 to call telephone 16,
25   a source and sink will be started on the telephone interface card 14 and connections will be established between telephones 11 and 16 as described above, this call will be given a specific call ID. As part of this process, local connection control 25 will maintain a table for this
30   call ID which associates the source and sink with the relevant connection that has been set up on bus 10, while local connection control 22 maintains a table for this call ID which associates the connection on bus 10 with the connection that has been set up on Ethernet 1 and so on.
35   Each device, e.g. network interface card, translates from one communication protocol to another as it passes from one media to another. By using this method, a communication

path is established between the telephones 11 and 16.
Equally, the connection routing tables could be maintained
in the central connection controller 24 using information
provided by the local connection controllers.

5   The most appropriate route is decided by the
connection controller 24 in accordance with a number of
predefined criteria. These criteria may include factors
such as the cost of the connection, the rate of data
transmission which is required, the time and date at which
10   the connection is made and the current utilization of the
network. Usually, the best connection is the one that
offers the fastest data transmission rate for the lowest
cost.

However, in certain circumstances, the user of the end
15   station may desire that a particular data transmission
speed or particular cost profile be met. This can be
achieved by having the user input any requirements on cost
or transmission rate when the call is initially requested.

CLAIMS

1. A communication system for establishing communication between two end points, the system comprising; at least two communication media operating in accordance with different communication protocols and connected to respective ones of the end points in use; an interface for coupling together the at least two communication media; and a control system connected to each of the end points and to the interface, wherein the control system is responsive to a request to establish a communication connection between the end points to configure the interface and the end points such that a connection path is defined between the end points, via the communication media along which messages can subsequently be sent.

2. A communication system according to claim 1, the control system comprising a connection controller coupled to at least the interface and the end points for determining possible connection paths between the end points, selecting one of the possible connection paths and configuring the end points and the interface to establish a connection between the end points, via the media, using the selected connection path.

3. A communication system according to claim 1 or claim 2, wherein the control system further comprises a number of local controllers, each local controller being coupled to the connection controller and to a respective one of the end points or the interface, wherein each local controller alters the configuration of the respective end point or interface in accordance with a request from the connection controller.

4. A system according to any of the preceding claims, wherein at least one of the communication media comprises a communication network.

5. A system according to claim 4, wherein the communication network operates under an ATM or token ring protocol.

6.   A system according to any of the preceding claims, wherein at least one of the communication media comprises a bus.

7.   A communication system according to at least claim 2,
5   the control system further comprising a call controller coupled to the two end points and the connection controller, the call controller being responsive to a request to establish communication between the end points to cause the connection controller to configure at least
10   the interface and the end points such that a connection path is defined between the end points via the two media.

8.   A method of operating a communication system for establishing communication between two end points, each end point being coupled to a respective communication medium,
15   the media operating in accordance with different communication protocols and being coupled together by an interface, the method comprising configuring the interface and the end points such that a connection path is defined between the end points, via the communication media along
20   which messages can subsequently be sent, characterised in that the method includes determining possible connection paths between the end points, selecting one of the possible connection paths, and configuring each end point and the interface to establish a connection between the end points,
25   via the media, using the selected connection path.

9.   A method according to claim 8 for operating a communication system according to any of claims 1 to 7.

1/1

Fig.1.

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6   H04L29/06   H04L12/66   H04L12/64

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6   H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 16007 A (FINLAND TELECOM OY ;KARHAPAEAE TUOMO (FI); SAKSANEN PAULI (FI)) 1 May 1997 cited in the application see page 3, line 21 - page 6, line 15 see page 8, line 10 - page 9, line 37 see page 10, line 31 - page 11, line 16 see page 12, line 33 - page 13, line 23 see claims 1,2,9,13; figure 1 ---	1-5,7-9
A	US 5 208 811 A (KASHIO JIRO ET AL) 4 May 1993 cited in the application see abstract see column 3, line 46 - column 5, line 17 see claims 1-11 ---	1-5,7-9
	-/--	

[X]	Further documents are listed in the continuation of box C.	[X]	Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
12 October 1998	20/10/1998

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Karavassilis, N

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication,where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 011, no. 351 (E-557), 17 November 1987 & JP 62 130049 A (TOSHIBA CORP), 12 June 1987 cited in the application see abstract ---	1-4,7-9
A	WO 96 38018 A (KOPONEN HARRI ;KAAKKOLA MATTI (FI); MELEN BJOERN (FI); VAEAENAENEN) 28 November 1996 see page 4, line 13 - page 5, line 9 see page 5, line 26 - line 35 see page 7, line 8 - line 26 see page 9, line 15 - line 21 see figures 1,2 ---	1-5,7-9
A	WO 97 01909 A (ERICSSON TELEFON AB L M) 16 January 1997 see abstract see page 1, line 21 - page 3, line 12 see page 4, line 20 - page 5, line 17 see page 6, line 3 - line 11 see page 9, line 13 - page 10, line 13 see page 17, line 9 - line 26 ---	1-4,7
A	MANIKOPOULOS C N ET AL: "PERFORMANCE ANALYSIS OF A GATEWAY CONNECTING THE CEBUS TO THE ISDN" IEEE TRANSACTIONS ON CONSUMER ELECTRONICS, vol. 39, no. 4, 1 November 1993, pages 870-877, XP000423076 see page 870, column 1, line 1 - page 871, column 1, line 15 -----	1,2,4,6

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9716007	A	01-05-1997	AU	7302596 A	15-05-1997
			FI	955810 A	26-04-1997
US 5208811	A	04-05-1993	JP	3148940 A	25-06-1991
WO 9638018	A	28-11-1996	FI	961690 A	25-11-1996
			AU	5916696 A	11-12-1996
			CA	2221183 A	28-11-1996
			CN	1185268 A	17-06-1998
			EP	0829181 A	18-03-1998
			NO	975343 A	21-01-1998
WO 9701909	A	16-01-1997	AU	6324196 A	30-01-1997
			EP	0835575 A	15-04-1998
			NO	976111 A	27-02-1998